

Electronic 0-10V Dimmable Drivers

120-277V LED Drivers

SPECIFICATIONS

Model	60 Watt	100 Watt	200 Watt (x2 100W Outputs)
Max Load	Acceptable load for any driver installed in an environment with an ambient temperature below 85°F (29°C) .		
	60 Watts	100 Watts	100 Watts per Output
	Recommended if the driver is installed in an environment with an ambient temperature between 85°F to 120°F (29°C to 49°C) .		
	54 Watts	90 Watts	90 Watts per Output
	Recommended if the driver is installed in an environment with an ambient temperature above 120°F (49°C) .		
Minimum Load	48 Watts	80 Watts	80 Watts per Output
	6 Watts	10 Watts	10 Watts per Output
Input Voltage	120-277VAC		90-305VAC
Output Voltage	24VDC		
Ambient Temperature Rating	-40°F to 194°F (-40°C to 90°C)		-40°F to 185°F (-40°C to 85°C)
Class 2 Compliant	Yes		
Dimming	0-10V <i>Compatible with most 0-10V dimmers.</i>		
Dimming Range (lumen output)	100% to 10%		100% to 1%
Dimensions (LxWxH)	9-1/2" x 4" x 2-7/16"	9-1/2" x 4" x 2-3/4"	12-1/4" x 4-1/2" x 2-3/8"
Weight	2 lbs. 2 oz.		5 lbs. 10 oz.
Average Efficiency	88%		91%
Wire Gauge Sizes	18AWG (input and output)		
Protections	Short Circuit, Open Circuit, Overload		
Environment	Indoor, Outdoor (non-submersible)		
Certifications	UL Listed (5GH6)		
Warranty	5 Year Limited		



60W & 100W Models



200W Model

ORDERING

Part Number	Capacity
DR-60W-24VDC-U-2-10-c	60W
DR-100W-24VDC-U-2-10-c	100W
DR-200W-24VDC-U-2-10-g	200W



CONTACT LED I

www.LED.I.LIGHTING
 Phone: (832) 717-2710
 Quotation requests: designs@ledinspirations.com

Version 10082021. Information subject to change without notice.
 Copyright © 2021 LED Inspirations, LLC. All rights reserved.

Project

Type

QTY

Signature
