

# Plug-In Drivers

## 120-240V Non-Dimmable LED Drivers

### SPECIFICATIONS

Model	36 Watt	96 Watt	144 Watt
Max Load	Acceptable load for any driver installed in an environment with an ambient temperature <b>below 85°F (29°C)</b> .		
	36 Watts	96 Watts	144 Watts
	Recommended if the driver is installed in an environment with an ambient temperature <b>between 85°F to 120°F (29°C to 49°C)</b> .		
	32 Watts	86 Watts	129 Watts
	Recommended if the driver is installed in an environment with an ambient temperature <b>above 120°F (49°C)</b> .		
	28 Watts	76 Watts	115 Watts
Minimum Load	4 Watts	10 Watts	14 Watts
Input Voltage	120-240VAC		
Output Voltage	24VDC		
Ambient Temperature Rating	-4°F to 176°F (-20°C to 80°C)		
Class 2 Compliant	Yes		No
Dimming	Non-dimmable		
Dimensions (LxWxH)	3-3/4" x 1-7/8" x 1-3/16"	5-1/8" x 2-5/16" x 1-1/4"	6-3/4" x 2-7/8" x 1-1/4"
Average Efficiency	84%	85%	84%
Connections & Lengths	Barrel Connector (3' 11") 2-Prong AC Wall Plug (6' 6") Zeus Connector Adapter (3-3/8") Zeus HD Connector Adapter (4-1/2")		
Protections	Short Circuit, Overload		
Environment	Indoor		
Certifications	UL Listed (E321192)		
Warranty	5 Year Limited		



### ORDERING

Part Number	Capacity
DR-36W-24VDC-120V-2-ND-e	36W
DR-96W-24VDC-120V-2-ND-e	96W
DR-144W-24VDC-120V-2-ND-e	144W



#### CONTACT LED I

www.LED.I.LIGHTING  
 Phone: (832) 717-2710  
 Quotation requests: designs@ledinspirations.com

Version 10082021. Information subject to change without notice.  
 Copyright © 2021 LED Inspirations, LLC. All rights reserved.

Project

Type

QTY

Signature