

QUANTUM 2 ANGLED 1005 CH-A-1005




Description

The Quantum 2 ANGLED 1005 Channel is a frosted lensed aluminum channel fixture that is powered by Quantum 2 High Density 08 LED tape light. It is dimmable, surface mountable and is perfect for lighting up cabinets and coves that need light at a 30 or 60 degree angle.

Specifications


Colors Available 2700K Ultra Warm White 3000K Warm White 3500K Neutral White 4000K Daylight White	Material	Anodized Aluminum	
	LED Chip	SMD 2835	
	Mounting	Surface Mount	
Lens Diffusion	50% (Some LEDs are visible)	Operating Temp.	32°F-122°F, relative humidity
Power Consumption	3 Watts/Foot	Max Length	8.2 FT
Input Voltage	24V DC	Dimensions WxH	1.0" x 0.5"
Lamp Life	50,000 Hours	Environment	Indoor, Dry
Color Tolerance	±100K	Certifications	 US LISTED
Light Distribution	120°	Warranty	5 Year Limited
Can It be cut?	Yes. Every 2-13/16" Inches	Dimming	Yes - See our Dimmer Compatibility List

COLOR (K)	LUMENS (per ft)	EFFICACY (LM/W)	CRI/Ra	R9	TM-30-15	
					Rf	Rg
4000K	287	96	90+	77	87	100
3500K	283	94	90+	77	87	100
3000K	273	91	90+	77	87	100
2700K	249	83	90+	77	87	100




Photometrics

Polar Candela Distribution




Illumination at a Distance

Beam Spread: 107°



Tested with a 1FT piece at 4000K

TM 30-15



Hue Bin	Fidelity Index	Chroma Change
1	84	-7%
2	85	0%
3	84	1%
4	90	2%
5	92	1%
6	94	-1%
7	89	-4%
8	84	-1%
9	86	-1%
10	80	1%
11	85	4%
12	91	5%
13	87	5%
14	91	1%
15	84	1%
16	92	-2%

ACCESSORIES QUANTUM 2 ANGLED 1005 CH-A-1005



Electronic MLV & Incandescent Dimmable 120VAC Drivers

20W, 40W, 60W, & 96W:
#DR-XXW-24VDC-120V-2-MLV



Electronic 0-10V Dimmable 120-277VAC Drivers

60&100W: #DR-XXW-24VDC-U-2-10
200W: #DR-200W-24VDC-U-2-10



Electronic Non-Dimmable 120-277VAC Drivers

60&100W: #DR-XXW-24VDC-U-2-10
200W: #DR-200W-24VDC-U-2-ND



Low Voltage Wire 12 AWG - 18 AWG CL3P

Contact our Design Team



Low Voltage Junction Box

#JBOX-1

For extending single color lead wires.

3 WAYS TO ORDER QUANTUM CHANNEL

1 Fixture Kit

An unassembled kit that includes an 8.2FT Channel , frosted lens, High Density LED tape light, driver and surface mount or recessed lighting hardware parts to build your own lighting fixture.

2 Standard Fixture

Standard preassembled fixture, driver & mounting hardware (except suspension kits) that is available in 2 foot, 4 foot, 6 foot, and 8 foot lengths.

3 Custom Fixture

Custom preassembled fixture, driver and mounting hardware. This fixture can be a custom length and powder coated to one of 192 RAL colors. Go to: www.ledi.lighting/custom to build your own custom Quantum Channel Fixture.

Driver Options

M120 = Magnetic/Incandescent TRIAC Dimmable 120V AC Input UL-Listed
 NDIM = Non-Dimmable Electronic 120-277V AC Input UL-Listed
 O10V = 0-10V Electronic 120-277V AC Input UL-Listed
 NONE = No driver option †

SKU Builder

Channel #	KIT/Length	Color	Driver Type	Suspension KIT
CH-A-0606C	KIT (Fixture Kit)	27 (2700K)	M120	O-33
CH-A-1005	2FT	30 (3000K)	NDIM	See next page for list of suspension kit options
CH-A-1212C	4FT	35 (3500K)	O10V	
CH-C-16*	6FT	40 (4000K)	NONE†	
CH-C-24*	8FT	RGB***		
CH-C-48*				
CH-R-1005	See next page for exact optimized lengths			
CH-R-1913				
CH-R-2513				
CH-R-3513				
CH-S-0304				
CH-S-0605				
CH-S-0808K**				
CH-S-1414**				
CH-S-1426**				
CH-S-1436**				
CH-S-1913**				
CH-S-1928**				
CH-S-2930**				
CH-T-2509*				

Notes:
 * Suspension Kits are REQUIRED for these channels.
 ** Suspension Kits are OPTIONAL for these channels.
 *** RGB is only compatible for these channel: CH-C-16, CH-C-24, CH-R-1913, CH-S-1414, CH-S-1426, CH-S-1436, and CH-T-2509.
Accessories Note: All Quantum Accessories such as RGB Components, Remotely Located Drivers and Channel Extension Pieces must be purchased separately.
 † **Driver Note:** If you want to use one driver to power more than one fixture then select the NONE driver type. You will have to contact our Design Team about your project so they can help you with selecting the correct remotely located drivers.
UL Listed Note: All our LED Drivers for the Custom Quantum Channel are UL Listed in the US and Canada.
Design Team Contact: Contact our Design Team for help via email: designs@ledinspirations.com or phone: 832-717-2710.

SUSPENSION KITS & CUT LENGTHS



Use the Suspension Kit # for ordering.

Suspension Kit #			Mounting	Shape/Size	Canopy Color	Dimensions (LxWxH)
6FT	12FT	25FT				
0 (No Suspension Kit)			-	-	-	-
1	2	3	Drywall	Round	Brushed Metal	5" x 5"
4	5	6	Drywall	Round	White	5" x 5"
7	8	9	Drywall	Round	Polished Nickel	5" x 5"
10	11	12	Drywall	Square	Brushed Metal	5" x 5"
13	14	15	Drywall	Square	White	5" x 5"
16	17	18	Drywall	Square	Polished Nickel	5" x 5"
19	20	21	Drop Ceiling	Round	White	5" x 5"
22	23	24	Drop Ceiling	Square	White	5" x 5"

Suspension kits come in 3 lengths: 6FT, 12FT, or 25FT.
For these suspension kits, the LED drivers must be remotely located.

Standard Fixture Optimized Lengths

In order to minimize shadow spots and create a more beautiful look we build each fixture to an optimized length closest to your desired length.

Channel #	2FT	4FT	6FT	8FT
CH-A-0606C	1' 11-1/32"	3' 9-1/2"	5' 10-13/16"	7' 9-9/32"
CH-A-1005	1' 11-1/32"	3' 9-1/2"	5' 10-13/16"	7' 9-9/32"
CH-A-1212C	1' 11-1/32"	3' 9-17/32"	5' 10-27/32"	7' 9-11/32"
CH-C-16	1' 11-1/2"	3' 10-7/16"	5' 9-13/32"	7' 11-5/8"
CH-C-24	1' 11-1/2"	3' 10-7/16"	5' 9-13/32"	7' 11-5/8"
CH-C-48	1' 8-7/32"	3' 11-3/4"	5' 11-3/8"	7' 10-31/32"
CH-R-1005	1' 11-11/32"	3' 9-13/16"	5' 11-3/32"	7' 9-19/32"
CH-R-1913	1' 8-3/4"	3' 11"	5' 9-15/16"	7' 8-29/32"
CH-R-2513	1' 8-29/32"	3' 8-17/32"	5' 8-5/32"	7' 11-23/32"
CH-R-3513	1' 8-29/32"	3' 8-17/32"	5' 8-1/8"	7' 11-11/16"
CH-S-0304	1' 11-1/32"	3' 9-1/2"	5' 10-13/16"	7' 9-9/32"
CH-S-0605	1' 11"	3' 9-1/2"	5' 10-25/32"	7' 9-9/32"
CH-S-0808K	1' 11-1/32"	3' 9-17/32"	5' 10-27/32"	7' 9-11/32"
CH-S-1414	1' 11-1/2"	3' 10-7/16"	5' 9-3/8"	7' 11-5/8"
CH-S-1426	1' 11-1/2"	3' 10-7/16"	5' 9-3/8"	7' 11-5/8"
CH-S-1436	1' 11-1/2"	3' 10-7/16"	5' 9-13/32"	7' 11-5/8"
CH-S-1913	1' 8-7/32"	3' 11-25/32"	5' 11-13/32"	7' 11-1/32"
CH-S-1928	1' 8-7/32"	3' 11-25/32"	5' 11-13/32"	7' 11-1/32"
CH-S-2930	1' 8-7/32"	3' 11-3/4"	5' 11-3/8"	7' 10-31/32"
CH-T-2509	1' 11-1/2"	3' 10-7/16"	5' 9-13/32"	7' 11-5/8"