

RGB T3 RF SYSTEM

REMOTE: #RGB-RF-CONT-T3M

AMPLIFIER: #RGB-RF-AMP-T3



Description

The RGB T3 RF System is used for controlling RGB tape light systems and can control up to 10 RGB zones. It has 18 preset scenes, including multi-color strobes and multi-color fades. The remote may also be programmed to control multiple amplifiers. Remote and amplifiers are sold separately.



Specifications

Remote		SEPARATELY		Amplifier	
Input	5V DC - Built-in Lithium Battery	Input		12-24V DC	
Working Current	<30mA	Output		12-24V DC	
Working Frequency	2.4GHz	Max Current Load		5A x 3 Channels	
RF Remote Distance	98 Feet	Max Output Power		12V: 180W, 24V: 360W	
RGB Modes	18	Working Temp.		-22°F to 131°F (-30°C to 55°C)	
Battery Capacity	1000mAh	Dimensions		8-5/16" x 1-9/16" x 1-3/16"	
Avg. Standby Time	6 Months	Touch Button Control		<ul style="list-style-type: none"> • On/Off • RGB Mode Pause • Move Forwards • Move Backwards • Speed + • Speed - • Brightness + • Brightness - 	
Avg. Usage Time	30 Days (Rechargeable with USB Cable)	Environment*		Indoor, Dry	
Remote Dimensions	5-11/16" x 2-3/16" x 7/8"	Certifications*			
Holder Dimensions	3-3/8" x 2-3/8" x 1-1/16"	Warranty*		5 Year Limited	

*Applicable to both components.

Wiring Diagram

